

SPECIFICATIONS PURSUANT TO CT6.74# - SLASH TREATMENT REQUIREMENTS (02/2002)

Leave Tops Attached (LTA), Units: All Skyline Units (1D, 1F, 3A, 6, 12B, 12C, 13A, 13C)

Purchaser shall leave the tops of felled trees attached to the top log and yard them to landings within the entire cutting unit as shown on the Sale Area Map.

Logs will be cut to not exceed 45 feet prior to yarding unless otherwise approved by the Forest Service.

Whole Tree Yarding (WTY), Units: All Tractor Units (1, 1B, 1C, 1E, 2, 2A, 3, 5, 7, 8, 9, 9B, 10, 10B, 10C, 10D, 12, 12A, 13, 13D, 13E, 13F, 13G, 13I, 13J, 14, 14A, 14B, 16, 16A, 16B, 16C, 16D, 16E, 16F, 17, 17A, 18, 18A, 24A, 25B, A1, A9, A11, A15, and A18).

Within units requiring whole tree yarding, accumulations of slash at the base of residual trees shall be removed and lop and scattered to a depth less than 24 inches in height.

Scatter Slash (SCAT), Units: All

Purchaser shall scatter all limbs cut from Included Timber, which remains in entire unit, so as to avoid concentrations around leave trees and to lie within 24 inches of the ground.

Pile Landing Slash (PL) Units: All

A landing is considered a place where any logs or products are gathered for loading. Slash and other debris resulting from Purchaser's operations that has accumulated on landings that is greater than 1 inch in diameter or greater than 8 feet in length shall be piled for burning by the Forest Service.

Construction of landing piles: Piles shall contain little or no soil. Accumulations of soil that remain after Forest Service Burning will be leveled to normal ground contour. Slash piling operations shall not unnecessarily damage young growth or other trees to be reserved. Slash piles shall be located away from residual trees and young growth to prevent damage during pile burning. All objects which extend more than 4 feet in any direction from the windrow or pile profile will be cut off and returned to the windrow or pile.